

SKYJACKER® WHEEL & TIRE SPECIFICATIONS

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Back Space
Chevrolet / GM / GMC							
07-18	K1500, Avalanche, Tahoe, SUV, Etc. (Coil-Over Assembly) ^{1,2,3}	2"	33"	11.5"	17-20"	8"	OEM
		4"	33"	12.5"	17-18"	8"	OEM
		6"	35"	12.5"	20"	8"	5.75"
00-06	Cadillac Escalade, ESV, EXT ^{1,3,4}	3"	33"	11.5"	17-18"	8-9"	5.5-5.75"
15-18	Colorado / Canyon 4WD	2"	32"	10"	16-20"	8-9"	4.5"-OEM
04-13	Colorado / Canyon 4WD ^{1,2}	4"	33"	11.5"	16-20"	8-9"	4.5"
00-06	Tahoe / Yukon / Suburban 4WD ^{1,2,4}	3"	33"	11.5"	16-20"	8-9"	4.5"-OEM
		6"	35"	12.5"	16-18"	8-9"	4.5"
00-06	Denali / Yukon XL 4WD ^{2,4}	3"	33"	11.5"	16-18"	8-9"	4.5-5.5"
02-06	Avalanche 4WD ^{1,2,4}	3"	33"	11.5"	16-20"	8-9"	4.5"-OEM
		6"	35"	12.5"	16-20"	8-9"	4.5"
02-08	Hummer H2 4WD	5.5"	38"	12.5"	16-20"	8-9"	4.5-5.5"
11-18	GM 2500HD / 3500HD 4WD ¹	2"	34"	12"	17"	8"	OEM
		6"	35"	12.5"	20"	9"	5.5"
		7"	37"	12.5"	17"	8"	5-5.26"
		7"	37"	12.5"	18"	8-9"	5-5.5"
		7"	37"	12.5"	20"	8.5-10"	5-6"
01-10	GM 2500HD / 3500HD 4WD ^{1,2,3}	3"	33"	11.5"	16-20"	8-9"	4.5"-OEM
		6"	35"	12.5"	16-18"	8-9"	4.5"
01-08	1500HD, 2500 ¹	6"	35"	12.5"	20"	8-9"	4.5-5.5"
99-06	K1500 IFS 4WD ^{1,2,3,4}	3"	33"	11.5"	16-18"	8-9"	4.5"
		6"	35"	12.5"	16-18"	8-9"	4.5"
88-98	Full-Size IFS 4WD ^{1,2}	2.5"	33"	11.5"	15-20"	8-9"	4.5"-OEM
		6"	35"	12.5"	15-20"	8-9"	4.5"
88-91	Full-Size Blazer, Jimmy, Suburban 4WD ¹	2.5"	33"	12.5"	15-20"	8-10"	3.5-4"
		4"	35"	12.5"	15-20"	8-10"	3.5-4"
		6"	37"	12.5"	15-20"	8-10"	3.5-4"
73-87	Full-Size 4WD ¹	4"	35"	12.5"	15-20"	8-10"	3.5-4"
		6"	37"	12.5"	15-20"	8-10"	3.5-4"
		8"	39"	12.5"	15-20"	8-10"	3.5-4"
67-72	Full-Size 4WD	2.5"	34"	12.5"	15-20"	8-10"	3.5-4"
		4"	36"	12.5"	15-20"	8-10"	3.5-4"
		6"	38"	12.5"	15-20"	8-10"	3.5-4"
		8"	40"	12.5"	15-20"	8-10"	3.5-4"
DODGE							
09-16	Ram Pickup 1500 4WD ³	4"	35"	12.5"	18-20"	8-10"	5"
		6"	37"	12.5"	18-20"	8-10"	5"
06-08	Ram Pickup 1500 4WD ³	2"	33"	12.5"	17-20"	8-9"	OEM
		4"	35"	12.5"	18-20"	8-10"	5"
		6"	37"	12.5"	18-20"	8-10"	5"
02-05	Ram Pickup 1500 4WD ²	6"	37"	12.5"	17"	9"	5"
14-18	Ram Pickup 2500 4WD ²	2"	33"	11.5"	18"	9"	4.5-5"
		4"	35"	12.5"	17-20"	8-9"	4.5"
		6"	37"	12.5"	17-20"	8-9"	4.5"
03-13	Ram Pickup 2500 4WD ²	3"	34"	12.5"	17-20"	8-10"	4.625"
		5"	37"	12.5"	17-20"	8-10"	4.625"

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Back Space
13-18	Ram Pickup 3500 4WD ²	2"	33"	11.5"	18"	9"	4.5-5"
		4"	35"	12.5"	17-20"	8-9"	4.5"
		6"	37"	12.5"	17-20"	8-9"	4.5"
03-12	Ram Pickup 3500 4WD ²	3"	34"	12.5"	17-20"	8-10"	4.625"
		5"	37"	12.5"	17-20"	8-10"	4.625"
94-01	Ram Pickup 4WD	2"-3"	33"	12.5"	15-20"	8-10"	4.625"
		4"-5"	35"	12.5"	15-20"	8-10"	4.625"
		7"	38"	12.5"	15-20"	8-10"	4.625"
61-93	Full-Size 1500, 2500 4WD	2"	33"	12.5"	15-20"	8-10"	4"
		4"	35"	12.5"	15-20"	8-10"	4"
		6"	37"	12.5"	15-20"	8-10"	4"
		8"	39"	12.5"	15-20"	8-10"	4"
FORD F-150, Bronco, Expedition							
09-18	F-150 4WD ²	2"	33"	12.5"	17-20"	8"	5"
		4.5"	34"	12.5"	20"	9"	5"
		6"	35"	12.5"	20"	9"	5"
04-08	F-150 4WD, 2WD ^{2,3,4}	2"-3"	33"	11.5"	17-20"	8-9"	4.5"-OEM
04-08	F-150 4WD, 2WD ²	6"	35"	12.5"	17-20"	8-9"	4.5"
97-03	F-150 4WD	6"	35"	12.5"	16-20"	8-9"	4.5"
92-96	F-150, Bronco 4WD, 2WD	2"	32"	12.5"	15-20"	8-10"	4"
		4"	33"	12.5"	15-20"	8-10"	4"
		6"	35"	12.5"	15-20"	8-10"	4"
		8"	37"	12.5"	15-20"	8-10"	4"
87-91	F-150, Bronco 4WD, 2WD	2"	34"	12.5"	15-20"	8-10"	4"
		4"	36"	12.5"	15-20"	8-10"	4"
		6"	38"	12.5"	15-20"	8-10"	4"
80-86	F-150, Bronco 4WD, 2WD	8"	39"	12.5"	15-20"	8-10"	4"
		2"	33"	12.5"	15-20"	8-10"	4"
		4"	35"	12.5"	15-20"	8-10"	4"
		6"	37"	12.5"	15-20"	8-10"	4"
69-79	F-150, 78-79 Bronco 4WD	8"	38.5"	12.5"	15-20"	8-10"	4"
		2"	33"	12.5"	15-20"	8-10"	4"
		4"	35"	12.5"	15-20"	8-10"	4"
66-77	Bronco 4WD with Cut-Outs	6"	37"	12.5"	15-20"	8-10"	4"
		9"	40"	12.5"	15-20"	8-10"	4"
		3"	33"	12.5"	15-20"	8-10"	4"
03-08	Expedition 4WD	5"	35"	12.5"	15-20"	8-10"	4"
		7"	37"	12.5"	15-20"	8-10"	4"
FORD F-250, F-350							
17-18	F-250, F-350 4WD Super Duty ²	2"	32"	12.5"	17-20"	9"	5"
		4"	33"	12.5"	17-20"	9"	5"
		6"	35"	12.5"	17-20"	9"	5"
		8"	37"	12.5"	17-20"	9"	5"
		8.5"	38"	12.5"	17-20"	9"	5"
05-16	F-250, F-350 4WD Super Duty ²	1"	32"	12.5"	17-20"	9"	5"
		2"	33"	12.5"	17-20"	9"	5"
		4"	35"	12.5"	17-20"	9"	5"
		6"	36"	12.5"	17-20"	9"	5"
99-04	F-250, F-350 4WD Super Duty	8.5"	38"	12.5"	17-20"	9"	5"
		2"	33"	12.5"	16-20"	8-10"	4.5-5"
		4"	35"	12.5"	16-20"	8-10"	4.5-5"
92-98	F-350 4WD Mono Beam	6"	36"	12.5"	16-20"	8-10"	4.5-5"
		8"	38"	12.5"	16-20"	8-10"	4.5-5"
		2"	34"	12.5"	16.5-20"	9.75"	4.625"
		4"	36"	12.5"	16.5-20"	9.75"	4.625"
		6"	38"	12.5"	16.5-20"	9.75"	4.625"

SKYJACKER® WHEEL & TIRE SPECIFICATIONS

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Back Space
86-91	F-350 4WD Mono Beam	2"	36"	12.5"	16.5-20"	9.75"	4.625"
		4"	38"	12.5"	16.5-20"	9.75"	4.625"
		6"	40"	12.5"	16.5-20"	9.75"	4.625"
92-98	F-250 4WD Twin I Beam	2"	33"	12.5"	16.5-20"	9.75"	4.625"
		4"	35"	12.5"	16.5-20"	9.75"	4.625"
		6"	37"	12.5"	16.5-20"	9.75"	4.625"
80-91	F-250, F-350 4WD Twin I Beam	2"	33"	12.5"	16.5-20"	9.75"	4.625"
		4"	35"	12.5"	16.5-20"	9.75"	4.625"
		6"	37"	12.5"	16.5-20"	9.75"	4.625"
92-96	F-250, F-350 2WD	2"	32"	12.5"	16-20"	8"	3.75"
		4"	34"	12.5"	16-20"	8"	3.75"
		6"	36"	12.5"	16-20"	8"	3.75"
78-79	F-250 Low Boy 4WD	2"	35"	12.5"	16.5-20"	9.75"	3.75"
		4"	37"	12.5"	16.5-20"	9.75"	3.75"
		6"	40"	12.5"	16.5-20"	9.75"	3.75"
66-77	F-250 High Boy 4WD	2"	38"	12.5"	16.5-20"	9.75"	3.75"
		4"	40"	12.5"	16.5-20"	9.75"	3.75"
FORD Ranger, Bronco II, Explorer, Navajo							
93-97	Ranger 4WD	2"	32"	12.5"	15-20"	8"	4"
		4"	33"	12.5"	15-20"	8"	4"
		6"	34"	12.5"	15-20"	8"	4"
		8"	36"	12.5"	15-20"	8"	4"
90-94	Explorer, Navajo 4WD	2"	31"	12.5"	15-20"	8"	4"
83-92	Ranger, Bronco II 4WD	2"	28"	12.5"	15-20"	8"	4"
		4"	30"	12.5"	15-20"	8"	4"
		6"	32"	12.5"	15-20"	8"	4"
HONDA							
06-12	Ridgeline 4WD ²	2"	30"	10.5"	17-20"	8"	5"
72-82	Scout II 4WD	2"	31"	12.5"	15-20"	8"	3.75"
72-82	Scout II 4WD	4"	33"	12.5"	15-20"	8"	3.75"
ISUZU							
05-08	Isuzu i-Series	4"	33"	11.5"	17-20"	8"	4.75"
JEEP							
07-18	Wrangler JK 2 Door & 4 Door ^{1,2}	2"	33"	12.5"	16-20"	8"	4.5"
		2.5-3.5"	34"	12.5"	16-20"	8"	4.5"
		4-5"	35"	12.5"	16-20"	8"	4.5"
		6-7"	37"	12.5"	16-20"	8"	4.5"
04-06	Wrangler Unlimited, Rubicon	2"	32"	11.5"	15-20"	8"	3.75"
		4"	34"	12.5"	15-20"	8"	3.75"
		6"	35"	12.5"	15-20"	10"	3.75"
		8"	37"	12.5"	15-20"	10"	3.75"
97-03	Wrangler TJ	2"	32"	11.5"	15-20"	8"	3.75"
		4"	34"	12.5"	15-20"	8"	3.75"
		6"	35"	12.5"	15-20"	10"	3.75"
		8"	37"	12.5"	15-20"	10"	3.75"
		10"	38"	12.5"	15-20"	10"	3.75"
87-96	Wrangler YJ	2"	31"	10.5"	15-20"	8"	3.75"
		4"	33"	12.5"	15-20"	8"	3.75"
		6"	35"	12.5"	15-20"	8"	3.75"
55-86	CJ & Scrambler	2"	31"	12.5"	15-20"	8"	3.75"
		4"	33"	12.5"	15-20"	10"	3.75"
05-12	Grand Cherokee WK 4WD, 2WD ²	2"	30.5"	9.5"	17-20"	8"	OEM
99-04	Grand Cherokee WJ 4WD	2"	31"	10.5"	16-20"	8"	3.75-4.5"

Vehicle		Lift	Maximum Tire			Wheel	
Year	Model		Height	Width	Diameter	Width	Back Space
93-98	Grand Cherokee ZJ 4WD, 2WD	3"	31"	10.5"	15-20"	8"	3.75-4.5"
08-12	Liberty 4WD, 2WD	2.5"	30.5"	10"	16-20"	8-9"	OEM
02-07	Liberty 4WD, 2WD ¹	2.5"	30.5"	10"	16-20"	8-9"	OEM
84-01	Cherokee XJ 4WD, 2WD	2"	30"	9.5"	15-20"	7-8"	3.75"
		3"	31"	10.5"	15-20"	8"	3.75"
		6"	33"	12.5"	15-20"	8"	3.75"
		8"	35"	12.5"	15-20"	8"	3.75"
06-10	Jeep Commander XK ²	2"	30.5"	9.5"	17-20"	8"	OEM
86-92	Comanche 4WD, 2WD	3"	31"	10.5"	15-20"	8"	3.75"
74-91	J10, J20, Cherokee, Wagoneer	4"	35"	12.5"	15-20"	10"	3.75"
NISSAN							
04-18	Titan 4WD ²	2.5"	33"	12.5"	17-20"	7"	OEM
04-11	Armada 4WD ²	2.5"	33"	11.5"	18-20"	7"	5
TOYOTA							
07-14	FJ Cruiser ²	2"	32"	10.5"	17-20"	8"	OEM
		3"	33"	11.5"	17-20"	8"	4.5
01-03	Sequoia 4WD	2.5"	32"	11.5"	16-20"	8"	3.5"
00-06	Tundra 4WD	2"	32"	11.5"	16-20"	8"	3.5"
		3"	32"	11.5"	16-20"	8"	3.5"
07-18	Tundra 2WD,4WD	2"	32"	11.5"	17-20"	9"	6"
		3"	32"	11.5"	17-20"	9"	6"
		6"	35"	12.5"	17-20"	8"	4.5"
		2"	31"	11.5"	16-20"	8"	4.5"
05-18	Tacoma 4WD, Pre-Runner 2WD ^{1,2}	2.5"-3"	33"	11.5"	16-20"	8"	5"
96-04	Tacoma 4WD, Pre-Runner 2WD ¹	2.5"-3"	32"	10.5"	15-20"	8"	4.5"
86-95	IFS Pickup 4WD	4"	33"	12.5"	15-20"	8"	3.75"
03-18	4Runner 2WD / 4WD ^{1,2}	2"	31"	11.5"	17-20"	8"	4.5"
		3"	33"	11.5"	17-20"	8"	4.5"
96-01	4Runner 4WD	2.5"	31"	11.5"	15-20"	8"	3.5"
84-85	Pickup, 4Runner 4WD	3"	33"	12.5"	15-20"	8"	3.75"
		5"	35"	12.5"	15-20"	8"	3.75"
		7"	37"	12.5"	15-20"	8"	3.75"
79-83	Pickup, 4Runner 4WD	3"	35"	12.5"	15-20"	8"	3.75"
		5"	37"	12.5"	15-20"	8"	3.75"
		7"	39"	12.5"	15-20"	8"	3.75"
91-97	FJ80 LandCruiser 4WD	2.5"	33"	12.5"	15-20"	8"	3.75"
64-80	LandCruiser 4WD	2"	32"	12.5"	15-20"	8"	3.75"
		4"	35"	12.5"	15-20"	8"	3.75"

¹ Footnote: Requires minor trimming.

² Footnote: If you change the Tire Diameter / Wheel Size on this application, you must still maintain the equivalent 'Section Width' & 'Overall Diameter' to the 'Height' & 'Width' dimensions listed in the chart. If 20" Diameter or larger wheels, OE back spacing may be used.

³ Footnote: Can use OEM Wheel

⁴ Footnote: If equipped with Factory 17" wheels, then must stay with 17" wheels or larger. Do Not downsize from OEM wheel size.

NOTE: This Chart is to be Used Strictly as a REFERENCE Due to Actual Lift Heights & Variances in Tire Sizes from Various Manufacturers.